



SAFETY DATA SHEET

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Preparation Date: 01/01/2019 Revision Date: N/A Revision Number: 1

SECTION 1 identification

1.1. Product Identifier

Trade Name or Designation: Nitric Acid 10% V/V

Product Number: APS15029

1.2. Recommended Use and Restrictions on Use

General Laboratory Reagent

1.3. Details of the Supplier of the Safety Data Sheet

Dawn Scientific Inc

121 Liberty Street, Metuchen, NJ, 08840 Tel: 732-902-6300 | Fax: 973-802-1005

sales@dawnscientific.com | www.dawnscientific.com

1.4. Emergency Telephone Number (24 hours)

CHEMTREC (USA) 800-424-9300 CHEMTREC (International) 1+ 703-527-3887

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Corrosive to metals Category 1 H290 May be corrosive to metals

Skin corrosion/irritation Category 1B H314 Causes severe skin burns and eye damage

Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage

Full text of H statements: see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms

(GHS US)



Signal word (GHS US) : D

Hazard statements (GHS US) : H290 - May be corrosive to metals

H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS US) : P234 - Keep only in original container.

P260 - Do not breathe mist, vapors, spray.

P264 - Wash exposed skin thoroughly after handling.

P280 - Wear protective gloves, protective clothing, eye protection, face protection. P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a poison center or doctor/physician.

P363 - Wash contaminated clothing before reuse.

P390 - Absorb spillage to prevent material-damage.

P405 - Store locked up.

P406 - Store in corrosive resistant container with a resistant inner liner.

P501 - Dispose of contents/container to comply with local, state and federal regulations.

2.3. Other hazards which do not result in classification

Other hazards not contributing to the : None.

classification

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Water	(CAS-No.) 7732-18-5	89-90
Nitric Acid, 70% w/w	(CAS-No.) 7697-37-2	10-11

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical

advice (show the label where possible). Call a physician immediately.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately

call a poison center or doctor/physician.

First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Immediately call a poison center or doctor/physician.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Immediately call a poison center or doctor/physician.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

Symptoms/effects : Causes severe skin burns and eye damage.

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : Burns. Yellow skin.

Symptoms/effects after eye contact : Causes serious eye damage. Corrosion of the eye tissue.

Symptoms/effects after ingestion : Burns.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Reactivity in case of fire : Reacts with organic material: (increased) risk of fire.

Hazardous decomposition products in case of : On heating/burning: release of toxic and corrosive gases/vapours (nitrous vapours). fire

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Do

not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Dike and contain spill. Absorb spillage to prevent material-damage.

6.1.1. For non-emergency personnel

Protective equipment : Protective goggles. Protective clothing. Gloves. Combined gas/dust mask with filter type B/P3.

Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes. Do

not breathe dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with

proper protection. For further information refer to section 8: "Exposure controls/personal

protection".

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or

diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

Absorb spillage to prevent material-damage.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : May be corrosive to metals.

Precautions for safe handling : Ensure good ventilation of the work station. Wash hands and other exposed areas with mild

soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe mist, vapors, spray.

Avoid contact with skin and eyes. Wear personal protective equipment.

Hygiene measures : Wash exposed skin thoroughly after handling. Wash contaminated clothing before reuse. Do

not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : incompatible

materials. Keep container closed when not in use. Store in corrosive resistant container with a resistant inner liner. Keep only in original container. Store in a well-ventilated place. Keep cool.

Store locked up.

Incompatible products : Strong bases. Halogens. metals. aluminum. Strong reducing agents.

Incompatible materials : Sources of ignition. Direct sunlight. Metals.

Packaging materials : Store in corrosive resistant container with a resistant inner liner.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Nitric Acid, 10% v/v (1+9)		
No additional information available		
Nitric Acid, 70% w/w (7697-37-2)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH TWA (ppm)	2 ppm (Nitric acid; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)	
ACGIH STEL (ppm)	4 ppm (Nitric acid; USA; Short time value; TLV - Adopted Value)	
USA - OSHA - Occupational Exposure Limits		
OSHA PEL (TWA) (mg/m³)	5 mg/m³	
OSHA PEL (TWA) (ppm)	2 ppm	

USA - IDLH - Occupational Exposure Limits		
US IDLH (ppm)	25 ppm	
USA - NIOSH - Occupational Exposure Limits		
NIOSH REL (TWA) (mg/m³)	5 mg/m³	
NIOSH REL (TWA) [ppm]	2 ppm	
NIOSH REL (STEL) (mg/m³)	10 mg/m³	
NIOSH REL (STEL) [ppm]	4 ppm	
Water (7732-18-5)		
No additional information available		

8.2. Appropriate engineering controls

Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate

vicinity of any potential exposure. Provide adequate general and local exhaust ventilation.

Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Combined gas/dust mask with filter type B/P3. Gloves. Protective clothing. Protective goggles.

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or face shield. Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

High gas/vapour concentration: gas mask with filter type E

Personal protective equipment symbol(s):









Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colorless to pale yellow liquid. Appearance Color Colourless to light yellow Odor : characteristic Pungent Odor threshold No data available рΗ : No data available Melting point : Not applicable Freezing point : No data available Boiling point : No data available Flash point No data available Relative evaporation rate (butyl acetate=1) : No data available : Non flammable. Flammability (solid, gas)

Vapor pressure : No data available Relative vapor density at 20 °C : No data available Relative density : No data available Specific gravity / density : 1.05 g/ml Solubility : Soluble in water. Log Pow : No data available : No data available Auto-ignition temperature Decomposition temperature : No data available Viscosity, kinematic : 0.99 mm²/s Viscosity, dynamic : No data available : No data available **Explosion limits** : No data available Explosive properties : No data available Oxidizing properties

9.2. Other information

VOC content : 0 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition generates: Corrosive vapors.

10.2. Chemical stability

Discolours on exposure to light.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong reducing agents. Strong bases. metals. aluminum. Ammonia. combustible materials. Halogens.

10.6. Hazardous decomposition products

Nitrogen oxides. Thermal decomposition generates: Corrosive vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Water (7732-18-5)	
LD50 oral rat	≥ 90000 mg/kg
ATE US (oral)	90000 mg/kg body weight
Skin corrosion/irritation	: Causes severe skin burns.
Serious eye damage/irritation	: Causes serious eye damage.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Viscosity, kinematic : 0.99 mm²/s

Likely routes of exposure : Inhalation. Skin and eye contact.

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

Symptoms/effects : Causes severe skin burns and eye damage.

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : Burns. Yellow skin.

Symptoms/effects after eye contact : Causes serious eye damage. Corrosion of the eye tissue.

Symptoms/effects after ingestion : Burns.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general

: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment. Before neutralisation, the product may represent a danger to aquatic organisms.

Nitric Acid, 70% w/w (7697-37-2)		
EC50 Daphnia 1	180 mg/l (EC50; 48 h)	
LC50 fish 2	72 ppm (LC50; 96 h)	
Threshold limit algae 1	> 19 mg/l (EC0)	

12.2. Persistence and degradability

Nitric Acid, 10% v/v (1+9)		
Persistence and degradability	Not established.	
Nitric Acid, 70% w/w (7697-37-2)		
Persistence and degradability	Biodegradability: not applicable. No test data on mobility of the components available.	
Biochemical oxygen demand (BOD)	Not applicable	
Chemical oxygen demand (COD)	Not applicable	
ThOD	Not applicable	
Water (7732-18-5)		
Persistence and degradability	Not established.	

12.3. Bioaccumulative potential

Nitric Acid, 10% v/v (1+9)		
Bioaccumulative potential	Not established.	
Nitric Acid, 70% w/w (7697-37-2)		
BCF fish 1	≤ 1 (BCF)	
Log Pow	-2.3 (OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method)	
Bioaccumulative potential	Bioaccumulation: not applicable.	
Water (7732-18-5)		
Bioaccumulative potential	Not established.	

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container to comply with local, state and federal regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN2031 Nitric acid other than (red fuming, with not more than 20 percent nitric acid), 8, II

UN-No.(DOT) : UN2031

Proper Shipping Name (DOT) : Nitric acid other than

red fuming, with not more than 20 percent nitric acid

Transport hazard class(es) (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Packing group (DOT) : II - Medium Danger Hazard labels (DOT) : 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx) : 158 DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Special Provisions (49 CFR 172.102) : A6 - For combination packaging, if plastic inner packaging are used, they must be packed in

tightly closed metal receptacles before packing in outer packaging.

B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized.

B47 - Each tank may have a reclosing pressure relief device having a start-to-discharge pressure setting of 310 kPa (45 psig).

B53 - Packaging must be made of either aluminum or steel.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T8 - 4 178.274(d)(2) Normal...... Prohibited

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP12 - This material is considered highly corrosive to steel.

DOT Packaging Exceptions (49 CFR 173.xxx) : None
DOT Quantity Limitations Passenger aircraft/rail : 1 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 30 L

CFR 175.75)

DOT Vessel Stowage Location

: D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger

vessels in which the limiting number of passengers is exceeded.

Other information : No supplementary information available.

Transport by sea

Transport document description (IMDG) : UN 2031 NITRIC ACID, 8 (5.1), II

UN-No. (IMDG) : 2031

Proper Shipping Name (IMDG) : NITRIC ACID

Class (IMDG) : 8 - Corrosive substances

Packing group (IMDG) : II - substances presenting medium danger

Subsidiary risks (IMDG) : 5.1 - Oxidizing substances

Air transport

Transport document description (IATA) : UN 2031 Nitric acid, 8, II

UN-No. (IATA) : 2031 Proper Shipping Name (IATA) : Nitric acid Class (IATA) : 8 - Corrosives Packing group (IATA) : II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Nitric Acid, 10% v/v (1+9)	
SARA Section 311/312 Hazard Classes	Health hazard - Skin corrosion or Irritation Health hazard - Serious eye damage or eye irritation Physical hazard - Corrosive to metals

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Nitric Acid, 70% w/w	CAS-No. 7697-37-2	9.5%	
Nitric Acid, 70% w/w (7697-37-2)			
RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb		
RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb		
SARA Section 302 Threshold Planning Quantity (TPQ)	1000 lb		
SARA Section 311/312 Hazard Classes	Physical hazard - Oxidizer (liquid, solid or Physical hazard - Corrosive to metals Health hazard - Skin corrosion or Irritation Health hazard - Serious eye damage or ey	,	

15.2. International regulations

CANADA

Water (7732-18-5)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 01/01/2019 Other information : None.

Full text of H-phrases: see section 16:

H272	May intensify fire; oxidizer
H290	May be corrosive to metals
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage

NFPA health hazard : 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

NFPA fire hazard : 0 - Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as

concrete, stone, and sand.

NFPA reactivity : 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.

: OX - Materials that posses oxidizing properties.



Hazard Rating

NFPA specific hazard

Health

given
: 0 Minimal Hazard - Materials that will not burn

Flammability
Physical

: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non violently with water or undergo

: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

hazardous polymerization in the absence of inhibitors.

Personal protection :

H - Splash goggles, Gloves, Synthetic apron, Vapor respirator

Last Revision Date: 01/01/2019

DISCLAIMER

When handled properly by qualified personnel, the product described herein does not present a significant health or safety hazard. Alteration of its characteristics by concentration, evaporation, addition of other substances, or other means may present hazards not specifically addressed herein and which must be evaluated by the user. The information furnished herein is believed to be accurate and represents the best data currently available to us. No warranty, expressed or implied, is made and Dawn Sciemtic Inc assumes no legal responsibility or liability whatsoever resulting from its use.